



SOLI - FORM 110 DOWN-UP 2 CIRCUIT 92767 DIM5 B-B

27143 9225 B-B

AVAILABLE IN
BLACK-BLACK 27143 9225 B-B
BLACK-FLEMISH GOLD 27143 9225 B-FG
WHITE-BLACK 27143 9225 W-B
WHITE-WHITE 27143 9225 W-W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.48 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC 2 CIRCUITS

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 14,1W / CRI>90 (R9: 50) / 2700K / 2026lm UP: LED cluster 14,1W / CRI>90 (R9: 50) / 2700K / 2026lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 2026lm // 14,1W // 144lm/W UP: 2026lm // 14,1W // 144lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 1722lm // 16W // 106lm/W UP: 1357lm // 16W // 84lm/W

Requirements
LED POWER SUPPLY 48V-DC

SOLI - FORM 110 DOWN-UP 2 CIRCUIT 92767 DIM5 B-B


27143 9225 B-B

For detailed installation instructions, please consult the manual: [27143_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

3




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

7



21012 0230 LED POWER SUPPLY 48V-DC / 100W

3




21012 0240 LED POWER SUPPLY 48V-DC / 200W

6


COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m





SOLI - FORM 110 DOWN-UP 2 CIRCUIT 92767 DIM5 B-B

27143 9225 B-B

Notes: