





INFORM 40 SQ 320 UP TW 850 DIM5 W-W

30732 8005 W-W

AVAILABLE IN
BLACK-BLACK 30732 8005 B-B
WHITE-WHITE 30732 8005 W-W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² 1,6m MELANOPIC LIGHT TECHNOLOGY

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 29,8W / CRI>80 (R9: 50) / 2700K-5000K / 3904lm Or @ 5000K: LED cluster 27W / CRI>80 (R9: 50) / 2700K-5000K / 4672lm
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 3904lm // 29,8W // 131lm/W Or @ 5000K: 4672lm // 27W // 173lm/W
LED TECHNICS (LUMINAIRE)	@ 2700K: 2571lm // 34W // 75lm/W Or @ 5000K: 3077lm // 31W // 99lm/W

Options



CABLE BASE R/S

INFORM 40 SQ 320 UP TW 850 DIM5 W-W
 30732 8005 W-W

For detailed installation instructions, please consult the manual: [30732_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO ☐
	203 99 55 B CABLE BASE R B ☐
	203 99 55 W CABLE BASE R W ☐
	203 99 56 ANO CABLE BASE S ANO ☐
	203 99 56 B CABLE BASE S B ☐
	203 99 56 W CABLE BASE S W ☐

Notes: