





OML50 CT - SPY 39 FOCUS 930 DIM5 B

31150 9305 B

AVAILABLE IN
BLACK 31150 9305 B
BRUSHED ALU 31150 9305 BRA
BRUSHED ANTHRACITE 31150 9305 BRAT
BRUSHED COPPER 31150 9305 BRCU
BRUSHED GOLD 31150 9305 BRG
BRUSHED OLD BRONZE 31150 9305 BROB
FLEMISH BRONZE 31150 9305 FBR
FLEMISH GOLD 31150 9305 FG
GOLD COLOURED 31150 9305 GC
WHITE 31150 9305 W



 [View on website](#)

General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	ADJUSTABLE BEAM 15°-45° for OMNILINER TRACK mounting

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W

Notes:

 DELTALIGHT®

OML50 CT - SPY 39 FOCUS 930 DIM5 B

31150 9305 B