



PARTOU FLAT OK 92736 S1 B

25220 9220 B



AVAILABLE IN

BLACK 25220 9220 B

FLEMISH BRONZE 25220 9220 FBR

FLEMISH GOLD 25220 9220 FG

WHITE 25220 9220 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	55
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 20° swiveling
INFORMATION	LENS FL-36° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	497lm // 7W // 75lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

Options

PLASTERKIT 101


CEILING COMPATIBILITY







Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	 PLASTERKIT 101 Required
 Wood	-
 Concrete + plaster	 PLASTERKIT 101 Required
 Lintel + plaster	 PLASTERKIT 101 Required
 Hollow-core slab + plaster	 PLASTERKIT 101 Required
 Stretched ceiling	-

PARTOU FLAT OK 92736 S1 B
25220 9220 B

FINISH YOUR SPECIFICATION


Emergency units

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

LED power supplies	#
	300 90 91 LED POWER SUPPLY 350mA-DC / 15W 2(1) ☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 2(2) ☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 2(2) ☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 1 ☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 2 ☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 1-2(2) ☐

PARTOU FLAT OK 92736 S1 B
25220 9220 B

Plasterkits



202 11 19 PLASTERKIT 101



Notes: