





DIRO SBL S IP 927 B

11436 9200 B

AVAILABLE IN
BLACK 11436 9200 B
WHITE 11436 9200 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 121
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP44
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 350mA-DC INCL.PC SBL

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED FLEX 5,9W / CRI>90 / 2700K / 900lm
LED TECHNICS (LIGHT SOURCE)	900 lm // 5,9 W // 153 lm/W
LED TECHNICS (LUMINAIRE)	338lm // 7W // 50lm/W

For detailed installation instructions, please consult the manual: [11436_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

Notes: