



ENTERO SQ-S TW 96520 FW

28504 9020 FW



AVAILABLE IN

BLACK 28504 9020 B

FULL WHITE 28504 9020 FW

GOLD COLOURED 28504 9020 GC

WHITE 28504 9020 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 76 x 76
RECESSED DEPTH (MM)	100
THICKNESS OF MOUNTING SURFACE (MM)	12,5 or 25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.24
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL. LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	845lm // 10W // 82lm/W

Requirements

LED POWER SUPPLY 500mA-DC TW

ENTERO SQ-S TW 96520 FW
28504 9020 FW

Accessories

- ENTERO S HONEYCOMB
- ENTERO S LINEAR SPREAD LENS
- ENTERO S SPREAD LENS
- ENTERO S SOFTENING LENS
- ENTERO S GLASS SBL

For detailed installation instructions, please consult the manual: [28504_XXX0_HAND.pdf](#)


CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

ENTERO SQ-S TW 96520 FW
28504 9020 FW

FINISH YOUR SPECIFICATION


LED power supplies #



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2 ☐

Light altering devices



28500 0010 ENTERO S LINEAR SPREAD LENS

☐




28500 0020 ENTERO S SPREAD LENS

☐




28500 0030 ENTERO S SOFTENING LENS

☐




28500 0040 ENTERO S GLASS SBL

☐



28500 0050 B ENTERO S HONEYCOMB SINGLE USE B

☐




28500 0060 B ENTERO S HONEYCOMB DOUBLE USE B


☐

ENTERO SQ-S TW 96520 FW
28504 9020 FW

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Notes: