





INFORM 40 SQ FI T PDS DOWN-UP TW 950 A-B

100093 9000 A-B

AVAILABLE IN
ALU GREY-BLACK 100093 9000 A-B
BLACK-BLACK 100093 9000 B-B
WHITE-BLACK 100093 9000 W-B



[View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Floor Stand alone
INGRESS PROTECTION	IP20
WEIGHT (KG)	10
ADJUSTABILITY	non adjustable
INFORMATION	INCL.1 x CABLE 3 x 0.75mm ² 2m + CEE 7/7 plug 3 control buttons : 1: UP ON/OFF + DIM 2: RECALL PRESENCE LEVEL + CHANGE CCT 3: DOWN+UP AUTO (sensor) / OFF + DIM INCL.PRESENCE & DAYLIGHT SENSOR PDS SETTINGS BY BLUETOOTH APP
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	control button on luminaire
ENERGY CLASS	D
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 14,5W / CRI>90 / 2700K-5000K / 201lm UP @ 2700K: LED cluster 48W / CRI>90 / 2700K-5000K / 7354lm Or DOWN @ 5000K: LED cluster 14,5W / CRI>90 / 2700K-5000K / 2245lm UP @ 5000K: LED cluster 48W / CRI>90 / 2700K-5000K / 8218lm
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 201lm // 14,5W // 139lm/W UP @ 2700K: 7354lm // 48W // 153lm/W Or DOWN @ 5000K: 2245lm // 14,5W // 155lm/W UP @ 5000K: 8218lm // 48W // 171lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 2700K: 1184lm // 17W // 71lm/W UP @ 2700K: 5192lm // 55W // 94lm/W Or DOWN @ 5000K: 1322lm // 17W // 79lm/W UP @ 5000K: 5802lm // 55W // 105lm/W

INFORM 40 SQ F1 T PDS DOWN-UP TW 950 A-B

100093 9000 A-B

Remarks

Bluetooth app

Options

INFORM 40 SQ F/T SWARM SENSOR

For detailed installation instructions, please consult the manual: [100093_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Miscellaneous control equipment




30710 0050 INFORM 40 SQ F/T SWARM SENSOR SET

☐

Other



30710 0060 INFORM 40 SQ F/T PDS REMOTE CONTROL

☐

30710 0070 INFORM 40 SQ F/T PDS PROGRAMMER

☐

Notes: