





INFORM 40 SQ FI T PDS DOWN-UP 930 A-B

100102 9300 A-B

AVAILABLE IN
ALU GREY-BLACK 100102 9300 A-B
BLACK-BLACK 100102 9300 B-B
WHITE-BLACK 100102 9300 W-B



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Floor Stand alone
INGRESS PROTECTION	IP20
WEIGHT (KG)	10
ADJUSTABILITY	non adjustable
INFORMATION	INCL.1 x CABLE 3 x 0.75mm ² 2m + CEE 7/7 plug 2 control buttons : 1: UP ON/OFF + DIM 2: DOWN+UP AUTO (sensor) / OFF + DIM INCL.PRESENCE & DAYLIGHT SENSOR SETTINGS BY INF40 SQ F/T PDS PROGRAMMER CONTROL BY INF40 SQ F/T PDS REMOTE CONTROL REMOTE CONTROL

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	control button on luminaire
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 16,4W / CRI>90 / 3000K / 2614lm UP: LED cluster 45,5W / CRI>90 / 3000K / 7891lm
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 2614lm // 16,4W // 160lm/W UP: 7891lm // 45,5W // 174lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 1540lm // 19W // 82lm/W UP: 5571lm // 52W // 106lm/W

Options

INFORM 40 SQ F/T SWARM SENSOR
 INFORM 40 SQ F/T PDS REMOTE CONTROL
 INFORM 40 SQ F/T PDS PROGRAMMER

INFORM 40 SQ F1 T PDS DOWN-UP 930 A-B
100102 9300 A-B

For detailed installation instructions, please consult the manual: [100102_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Miscellaneous control equipment




30710 0050 INFORM 40 SQ F/T SWARM SENSOR SET

☐

Other



30710 0060 INFORM 40 SQ F/T PDS REMOTE CONTROL

☐

30710 0070 INFORM 40 SQ F/T PDS PROGRAMMER

☐

Notes: