





OBIN ON 2 92724 DIM5 B
 30512 9225 B

AVAILABLE IN
BLACK 30512 9225 B
WHITE 30512 9225 W




[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.4
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	2 x LENS FL-24° INCL.DIMMABLE POWER SUPPLY

Electrical info

ELECTRICAL	120-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm)
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2916lm // 23,2W // 125lm/W
LED TECHNICS (LUMINAIRE)	2434lm // 27W // 91lm/W

Requirements

SPY 90 TUBE

Accessories


HONEYCOMB 75

OBIN ON 2 92724 DIM5 B
 30512 9225 B

For detailed installation instructions, please consult the manual: [30512_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices




13

19810 0110 B
HONEYCOMB 75 SINGLE USE B

☐

Finish your product

 28 19810 0170 B SPY 90 TUBE B ☐
19810 0170 DC SPY 90 TUBE DC ☐
19810 0170 FBR SPY 90 TUBE FBR ☐
19810 0170 FG SPY 90 TUBE FG ☐
19810 0170 GC SPY 90 TUBE GC ☐
19810 0170 W SPY 90 TUBE W ☐

Notes: