





SPY 52 HE 92720 ADM B

19801 9220 B

AVAILABLE IN
BLACK 19801 9220 B
FULL WHITE 19801 9220 FW
WHITE 19801 9220 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	LENS FL-20° 3F MULTI POWER ADAPTER 350mA

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 2700K / 905lm
TM-30 VALUES	rf: 96 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	905lm // 6W // 150lm/W
LED TECHNICS (LUMINAIRE)	733lm // 7W // 106lm/W

Requirements

SPY 52 TUBE
 TRACK 3F DIM

For detailed installation instructions, please consult the manual: [19801_XXX0_HAND.pdf](#)

SPY 52 HE 92720 ADM B
19801 9220 B

FINISH YOUR SPECIFICATION

Finish your product

	19810 0100 B SPY 52 TUBE B	☐
	19810 0100 FBR SPY 52 TUBE FBR	☐
	19810 0100 FG SPY 52 TUBE FG	☐
	19810 0100 GC SPY 52 TUBE GC	☐
	19810 0100 W SPY 52 TUBE W	☐

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410 TRACK 3F DIM H 1m	1000 m	1.6 kg	☒ ☐
200 14 420 TRACK 3F DIM H 2m	2000 m	3.2 kg	☒ ☐
200 14 430 TRACK 3F DIM H 3m	3000 m	4.8 kg	☒ ☐
TRACK 3F DIM IN			Available Colours
200 13 410 TRACK 3F DIM IN 1m	1000 m	1.2 kg	☒ ☐
200 13 420 TRACK 3F DIM IN 2m	2000 m	2.4 kg	☒ ☐
200 13 430 TRACK 3F DIM IN 3m	3000 m	3.5 kg	☒ ☐
TRACK 3F DIM ON			Available Colours
200 12 410 TRACK 3F DIM ON 1m	1000 m	1.1 kg	☒ ☐
200 12 420 TRACK 3F DIM ON 2m	2000 m	2.1 kg	☒ ☐
200 12 430 TRACK 3F DIM ON 3m	3000 m	3.1 kg	☒ ☐



SPY 52 HE 92720 ADM B

19801 9220 B

Notes: