




SPY 52 ON 2 HE 92720 DIM8 B-B
19805 9228 B-B

AVAILABLE IN
BLACK-BLACK 19805 9228 B-B
FULL WHITE 19805 9228 FW
WHITE-WHITE 19805 9228 W-W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	LENS FL-20° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 6W / CRI>90 (R9: 50) / 2700K / 905lm)
TM-30 VALUES	rf: 96 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1810lm // 12W // 150lm/W

Requirements	
SPY 52 TUBE	


For detailed installation instructions, please consult the manual: [19805_XXX8_HAND.pdf](#)

SPY 52 ON 2 HE 92720 DIM8 B-B

19805 9228 B-B

FINISH YOUR SPECIFICATION

Finish your product

	19810 0100 B	SPY 52 TUBE B	☐
	19810 0100 FBR	SPY 52 TUBE FBR	☐
	19810 0100 FG	SPY 52 TUBE FG	☐
	19810 0100 GC	SPY 52 TUBE GC	☐
	19810 0100 W	SPY 52 TUBE W	☐

Notes: