





SPY 52 ST HE 92720 W-W

19806 9220 W-W

AVAILABLE IN
WHITE-WHITE 19806 9220 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 98
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS FL-20° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 2700K / 905lm
TM-30 VALUES	rf: 96 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	905lm // 6W // 150lm/W
LED TECHNICS (LUMINAIRE)	733lm // 7W // 106lm/W

Requirements

SPY 52 TUBE
LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual: [19806_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Stretched ceiling	-

SPY 52 ST HE 92720 W-W

19806 9220 W-W

FINISH YOUR SPECIFICATION

Emergency units




21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐


LED power supplies #



300 90 91 LED POWER SUPPLY 350mA-DC / 15W

1->2(1)


☐



300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8

1


☐



300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8

2 -> 2


☐



21012 0515 LED POWER SUPPLY MULTI POWER DIM5

1(1)


☐



21012 0520 LED POWER SUPPLY 350mA-DC / 8W

1(0)

☐



21012 0575 LED POWER SUPPLY MULTI POWER DIM5

2->3(2)


☐

⌵ DELTALIGHT®

SPY 52 ST HE 92720 W-W

19806 9220 W-W

Finish your product

	19810 0100 B	SPY 52 TUBE B	☐
	19810 0100 FBR	SPY 52 TUBE FBR	☐
	19810 0100 FG	SPY 52 TUBE FG	☐
	19810 0100 GC	SPY 52 TUBE GC	☐
	19810 0100 W	SPY 52 TUBE W	☐

Notes: